# DT50 Accessories Brochure

# All Accessories

Multi-Slot Cradle 1

Multi-Slot Cradle 2

Multi-Slot Cradle 3

4-Slot Battery Charging Cradle

Optical Fingerprint Module

Trigger Handle

Power Adapter

Battery (4300mAh standard)

USB Cable

Battery (6000mAh optional)

# All Accessories

Two-tone Protective Shell

UHF Handle

Protective Cover

Holster

Multi-function Cradle

Power Adapter

Charging Cradle



Screen Protector

Hand Strap

# Standard Accessories

## Adapter

- Quick charge 3.0 USB charger
- Input: 100-240V~50/60Hz 0.6A MAX
- Output: 5V/3A, 9V/2A, 12V/1.5A

## USB Cable

- Applicable for charging and data transmission
- Interface : Type-C

## Battery

- Polymer li-ion battery
- 3.85V 4300mAh
- Hours of operation: More than 10 hours
- Charging time: Less than 3 hours

# Optional Accessories

## Charging Cradle

- Input: : 12V/2A
- Interface: DC Jack
- Life cycle: 5000 times

## **Power Adapter** (Charging Cradle)

- Applicable for charging device with country specific plugs.
- Input:100-240V~50/60Hz 0.4A
- Output: 12V/2A

## Charging Cradle

Charge 1 × device and 1 × battery simultaneously

Support TPU protective cover

# Multi-function Cradle

- 12V/2A DC Jack charging port
- Type-c data interface
- Charge 1 × device and 1 × battery simultaneously (support two-tone protective shell)

## 4-Slot Battery Charging Cradle

- Input: 12V/3A
- Interface: DC Jack
- Life cycle: 5000 times

## Power Adapter (4-Slot Battery Charging Cradle)

- Applicable for charging device with country specific plugs.
- Input: 100-240V~50/60Hz 0.4A
- Output: 12V/3A

## 4-Slot Battery Charging Cradle

Charge 4 × spare batteries simultaneously

148 (L) ×104 (W) ×96.5 (H) mm

# Multi-Slot Cradle

## 5BCDT5001

Multi-Slot Cradle for 5 x DT50 Series

516.2 (L) × 148 (W) ×101 (H) mm

## 5BCDT5002

Multi-Slot Cradle for 4 x DT50 Series

plus 4 x spare batteries

516.2 (L) × 148 (W) × 101 (H) mm

# Multi-Slot Cradle

5BCDT5003

5-Slot Ethernet Cradle for 5 x DT50 Series

516.2 (L) ×148 (W) ×197 (H) mm

Ethernet module integrated into the bottom of the cradle

## Required for Multi-Slot Cradle

- Applicable for charging device with country specific plugs
- Input: 100-240V 50/60Hz
- Output: 12V/10A
- Provide high density & flexibility
- Available in charge-Only or ethernet feature
- Charge multiple terminals and batteries simultaneously

# Trigger Handle

| | |
|---|---|
| Working temperature | -20℃ ~ 60℃(-4℉-140℉) |
| Storage temperature | -40℃ ~ 70℃(-40℉-158℉) |
| Humidity | 5%RH ~ 95%RH<br>( No condensation ) |
| Life cycle | Over 30000 times |

- Efficient scanning
- Easy assembly and disassembly
- Manipulating ease and comfort grip

# UHF Handle

- UHF Protocol:EPC Global Class1 Gen2/ISO 18000-6B/6C
- Frequency:902-928MHz and 865-868MHz
- Reading distance:Up to 8 meters (open environment)
- Group Reading Performance:>200 labels/sec
- Built-in 3000mAh battery
- Type C Interface
- Support PSAM, Class A/B/C
- Trigger button *1, Power button *1 (left), Mode button *1 (right)

# Optical Fingerprint Module

- 360 ° recognition
- Dry/wet, deep/shallow fingerprints identification
- 3D fingerprint imaging
- FIPS-201(PIV) compliance certification from the FBI
- FBI mobile ID FAP20 compliance certification from the FBI
- Live finger detection

**Optical Fingerprint Module**

( Integrated with battery cover )

# Screen Protector & Hand Strap

- Improve protection performance
- Convenient for mobile operation and carrying

Country specific power supplies would be option.

# Battery, Holster, Protective Cover,Two-tone Protective Shell

- Battery:Removable 3.85V 6000mAh lithium-ion battery(Need to replace the battery back cover)
- Holster:Easy to carry around
- Protective Cover:Enhance the protection of device
- Two-tone Protective Shell:Hard material, support hand strap

Country specific power supplies would be option.