

Industrial Panel PC EM-PPC10J/PPC15J/PPC21J



Product Feature:

- Intel Celeron N5100
- Windows 10 OS
- Fanless with low consumption
- IP65 of front panel
- DC 12V/19V/24V

Ordering Information:

Model	Parameter	Configuration
EM-PPC10J	CPU	Intel® N5100, up to 2.80GHz
	Memory	DDR3L 4GB
	USB	2 x USB3.0, 2 x USB2.0
	OS support	Windows 10
Model	Parameter	Configuration
EM-PPC15J	CPU	Intel® N5100, up to 2.80GHz
	Memory	DDR3L 4GB
	USB	2 x USB3.0, 2 x USB2.0
	OS support	Windows 10
Model	Parameter	Configuration
EM-PPC21J	CPU	Intel® N5100, up to 2.80GHz
	Memory	DDR3L 4GB
	USB	2 x USB3.0, 2 x USB2.0
	OS support	Windows 10

Specification Parameter

System Parameter	CPU	Intel® Celeron N5100 CPU, up to 2.80GHz
	Chipset	Intel UHD
	RAM	Onboard 4GB
	Storage	64GB
	I/O	2 x USB3.0, 2 x USB2.0
		2 x DB-9, RS232
		2 x RJ45 (10/100/1000M)
		1 x Audio Output
		1 x HDMI
		1 x SIM
1 x WiFi/BT5.0		
Expansion Slot	M2 x 1	
OS	Windows 10	
Display	Size	10.1" TFT-LCD 10 : 16 (EM-PPC10J)
		15.6" TFT-LCD 16 : 9 (EM-PPC15J)
		21.5" TFT-LCD 16 : 9 (EM-PPC21J)
	Resolution	800 x 1280 (EM-PPC10J), 1920 x 1080 (EM-PPC15J/PPC21J)
	Brightness	450cd/m² (EM-PPC10J), 250cd/m² (EM-PPC15J/PPC21J)
Touch Panel	10 point capacitive touch screen	
Power	DC	AC100V ~ 240V, 50Hz/60Hz, DC 12V/4A
Product Form	Dimension	257.2 x 170 x 45.95 mm (EM-PPC10J)
		388.63 x 248.43 x 54.95 mm (EM-PPC15J)
		537.02 x 324.02 x 57.60 mm (EM-PPC21J)
Device Color	black	
Weight	1.2Kg (EM-PPC10J), 2.4Kg (EM-PPC15J), 5.05Kg (EM-PPC21J)	
Reliability	IP Code	IP65 of front panel
	Operate Temperature	-20°C to 60°C
	Store Temperature	-30°C to 70°C
	Humidity	95%@40°C, Non-Condensing