

UROVO

RFG91

UHF RFID Sled(POGO PIN Version)



Effortless POGO PIN Connection

Features a POGO PIN interface, enabling seamless, tool-free connection with compatible mobile devices.

Expandable Long Distance RFID

The DT610 pairs with the RFG91 RFID sled to extend reading distance > 15m, it delivers a faster RFID reading rate of 1300+ tags per second .

Lightweight, Perfect in Hand

Supports fast attachment/detachment while maintaining a secure fit, offering enhanced flexibility and efficiency in demanding work environments.

Flexible Battery Options

Standard 5000mAh removable battery, with an optional 6700mAh high-capacity battery, supporting battery management, offering flexible endurance for various scenarios.



400g



UHF RFID Reading



5000mAh/6700mAh Smart Battery



IP67 Sealing

RFG91 UHF RFID Sled(POGO PIN Version)

UROVO

Specifications

Standards Supported

EPC Global Class1 Gen2/
ISO 18000-6C

Frequency Range

902-928MHz
865-868MHz

Read range

Over 15 meters
*Data from UROVO Lab

Read Rate

1300+ tags/sec
*Data from UROVO Lab

Dimensions

171mmx149mmx80mm
Weight: 400g

Battery

Standard: 3.6V, 5000 mAh
Extended: 6700 mAh (Optional)

Interface

USB Type-C

LED Indicators

Power Indicator Light
Decoding Status Lights*2
Bluetooth Reset Light*1
Mode Light*1

Protection

IP67 dustproof and waterproof
1.5m drop resistance

Environment

Operation Temp.: -20 ~ +60°C
Storage Temp.: -40 ~ +70°C
Humidity: 5%RH ~ 95%RH(No condensation)
ESD: ±15KV Air discharge, ±8KV Direct discharge

UROVO PTE. LIMITED

Website: en.urovo.com
Email: urovo@urovo.com
Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,
Singapore 048616

Urovo Europe

Website: europe.urovo.com
Email: sales-europe@urovo-emea.com
Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America

Website: us.urovo.com
Email: urovo@urovo.com
Address: 1990 Main Street, Suite 750, Sarasota,
Florida 34236

*This page is subject to change
without prior notice